999.00 EUR
incl. 19% VAT, plus shipping

- Fanless !
- Auto Power On/Off !
- CAN-BUS 2.0B
- 3x RS232 !

**Support:** Device Specification | CAN-BUS Manual [EN] | Manual [EN] | Drivers (Windows) | Internal GPS Module | Drivers (CAN-BUS) | Drivers (GPS)

This MiniPC was especially designed for fleet applications. The Car-PC can be connected directly to the car battery (12V/24V). Based on ignition plus, the PC will start and shutdown.

For a full PC you need in addition :
- 2.5" HDD/SSD or CompactFlash

The PC is completely fanless and is equipped with an AMD G-T56N 2x1.6GHz CPU.

**Available additional modules:**
The PC comes with 4x antenna-output and 3x Mini-PCIe slots.
We recommend these modules:
- HSPA / UMTS / EDGE Mini-PCIe Modem (Huawei EM770W)
- Wireless LAN / Bluetooth Mini-PCI Express [Qcom Combo]

**Features :**
- Fanless
- AMD G-T56N Dual Core CPU
- AMD Radeon HD 6320 Graphics
- GPS (Atheros Chipsatz)
- 1x CAN BUS 2.0B
- 3x RS232
- 2x Gigabit LAN
- DVI-I + DSUB-15 VGA

- Watchdog
- Prepared for GPS, WLAN, GSM/GPRS with ext. antennas
- 2 x DI / 2 x DO with Relay 12V / 100mA
- Vibration/shock tested

For FleetPC-5 we offer an direct connector cable for our TFT-dispays.

| | |
|---|---|
| Dimensions / Weight | 235mm W x 155mm D x 55mm H, 1.5kg |
| CPU | AMD G-T56N Dual Core 2x 1.65GHz |
| Chipset / FSB | AMD A55E Controller Hub |
| RAM | 2x SO-DDR-3 RAM (up to 8GB 1333Mhz) |
| Graphics | AMD Radeon HD 6320 |
| GPS | Locosys LS26050 |
| Expansion | - 3x Mini-PCIe |
| OS Support | Windows XP Home/Pro/Embedded, Windows 7/8, Linux |
| Vibration & Shock | MIL-STD-810F |
| Operating temperature | -30~60°C (with SSD) |
| Certification | CE, FCC, eMark (2009/19/EC, CISPR 25:2008, ISO 7637-2:2004), Railway EN50155 |
| I/O | - 2x Gigabit LAN (Realtek RTL8111E)<br>- 3x RS232 (2x with RS-422/485)<br>- 4x USB2.0<br>- GPIO port (2in, 2out, with Relay 12V/100mA)<br>- SPK Out<br>- 1x DVI + 1x DSUB-15 VGA<br>- 4x SMA Antenna hole (for eg. GPS, GSM/GPRS/3G, WLAN, Bluetooth) |
| Drive bays | 1 x 2.5" SATA HDD/SSD drive bay |
| Power supply | 9~32V DC PSU included<br>- Power off Delay Time Setting by Software, Default 5min<br>- Backup Battery Kit (optional) |
| Scope of supply | - FleetPC-5 PC with AMD G-T56N (2x1.6Ghz), mounting<br>- 1x Pigtail + antenna for GPS |