



119.00 EUR
incl. 19% VAT, plus [shipping](#)

- USB 3.0 !
- eSATA 3G / 6G !
- 4x 3.5" HDD !
- 150W !



External enclosure for 4x 3.5" HDD drives. USB3.0 and eSATA (3G/6G) interface. Perfect for NAS.

Features :

- Supports SATA III transfer rate of 6.0Gbps, 3.0Gbps 1.5Gbps
- Flexible connection via eSATA or USB host port
- Provides 1 eSATA host port

eSATA Compliance:

- Compliant with Serial ATA Port Multiplier Spec. Revision 1.2
- Compliant with Serial ATA PHY Selector Spec. Revision 1.0
- Compliant with Serial ATA PHY Electrical Spec. Revision 1.0
- Compliant with Serial ATA High Speed Serialized AT Attachment Spec. Revision 3.1
- Auto-negotiation support for 1.5Gbps / 3.0Gbps/ 6.0Gbps SATA
- Output swing control and automatic impedance calibration for SATA III PHY
- Supports PM aware and non-PM aware host on RAID mode

- Supports 48-bit LBA addressing
- Support for FIS-based switching and command-based switching SATA host controllers
- SATA Hot-plug capability
- Supports ATAPI drives
- Supports BIST and loopback mode
- Provides 1 USB host port

USB Compliance:

Compliance with USB2.0 and 3.0 specifications.

Compliance with USB Mass Storage Class, Bulk-Only Transport Specification.

- Operates at USB low speed and super speed rates (1.5Mb ~ 5Gb/s)
- Support on line USB firmware update
- Supports and compatible with OHCI/UHCI/EHCI hosts
- Support Mass Storage Class
- No software driver needed for Windows 98, ME, 2000, 2003, XP, Windows 7, Linux and Mac OS
- Provides status (Link & Activity) for Host and Device ports & Power On LEDs
- Dissipates heat efficiently with metal housing
- Maximizes airflow with silent, high quality fan

Color	Black
Body	SECC
Front panel	ABS
Dimension	265mm (D) x 186mm (H) x 135mm (W)
Drive bay	3.5" HDD x 4 (no trays included)
Cooling fan	8cm x 1
Status indicator	4x HDD Leds / Power Led
Power supply	150W
OS Support	Windows 98, ME, 2000, 2003, XP, Windows 7, Linux and Mac
I/O interface	USB3.0 & eSATA
SATA features	6.0Gbps SATA III Port Multiplier