



999.00 EUR incl. 19% VAT, plus shipping

- Fanless ! GPS !
- Auto Power On/Off !
- eMark certified !
- VBOX-3140

Support: Specifications | Test Tools | Drivers

This MiniPC was especially designed for fleet applications. The Car-PC can be connected directly to the car battery (12V/24V). Based on ignition plus, the PC will start and shutdown.

For a full PC you need in addition :

- 2.5" HDD/SSD or SATA DOM module

The PC is completely fanless and is equipped with an Intel Apollo Lake N3940 4x1.8GHz CPU and 4GB RAM.

Available additional modules:

The PC comes with 4x antenna-output, 2x Mini-PCIe slots (1x occupied by GPS module) and 1x M.2 Slot.

We recommend these modules:

- HSPA / UMTS / EDGE Mini-PCIe Modem (Huawei MU609)
- Wireless LAN / Bluetooth Mini-PCI Express [Qcom Combo]

Features :

- Fanless
- Intel Apollo Lake N3940 Quad Core CPU 4x1.8GHz CPU
- Integrated, intelligent Automotive power supply
- 3x RS232
- GPS (ublox 6 with G-sensor)
- 2x Gigabit LAN
- DVI-I + HDMI
- Watchdog
- Prepared for GPS, WLAN, GSM/GPRS with ext. antennas
- 2 x DI / 2 x DO with Relay 12V / 100mA
- Vibration/shock tested

For FleetPC-4-E we offer an direct connector cable for our TFT-dispays.



FleetPC-4-E Car-PC (Intel Apollo Lake N3940 4x1.8Ghz, 4GB RAM, Autostart-Controller, 9-36V Automotive
PSU, GPS) [FANLESS]
[http://www.cartft.com/catalog/il/2324]

CPU	Intel Apollo Lake E3940 Quad Core 4x1.8GHz
RAM	1x SO-DDR-3L RAM (up to 8GB) [4GB RAM included]
Graphics	Intel HD Graphics 500
GPS	VDB-810G (ublox M8 with G-sensor)
Expansion	- 2x Mini-PCIe, 1x M.2
OS Support	Windows 10, Linux
Vibration & Shock	MIL-STD-810F
Operating temperature	-40~70°C (with SSD)
Certification	CE, FCC, eMark
	- 2x Gigabit LAN (Intel i210-AT)
	- 3x RS232 (2 with 232/422/485)
	- 2x USB3.0
	- 1x USB2.0
I/O	- GPIO port (2in, 2out, with Relay 12V/100mA)
	- Mic-In, SPK Out
	- 1x DVI-I (for DVI-D and VGA), 1x HDMI
	- 4x SMA Antenna hole (for eg. GPS, GSM/GPRS/3G, WLAN,
	Bluetooth)
Drive bays	1 x 2.5" SATA HDD/SSD drive bay, 1x SATA DOM
	9~36V DC PSU included
Power supply	- Power off Delay Time Setting by Software, Default 5min
	- Backup Battery Kit (optional)
Scope of supply	- FleetPC-4-E PC with Apollo Lake E3940 (4x1.8Ghz), 4GB RAM,
	mounting adapter
	- 1x Pigtail + Antenna for GPS