



79.95 EUR incl. 19% VAT, plus shipping

Support: The Datasheet | The Brochure | Example Libaries

Expansion Module Adding functions for controllers NORVI is always about on connectivity and expandability. This is the time to make use of Expansion port of NORVI Controllers. The series of expansion modules connects to NORVI IoT controllers via its I2C and UART connections. You can add more features to the NORVI Controller without huge customizations. NORVI provides true technology with reliability for industrial applications being worlds iot hardware manufacturer. We have included NB-IoT, LoRa and analog modules as expansions.

- 4 channel 0 10V inputs with ADS1115 16 bit ADC
- I2C Interface with controller
- Input voltage range upto 10V
- · Over voltage protection
- Programmable Gain Amplifier

Main	
Range of product	NORVI Expansion
Product type	Expansion Module - NORVI-EX-ANV01
Rated supply voltage	12 - 24V DC
Field of Application	Voltage measurement
Applicable Devices	NORVI IIOT / NORVI Arita
Aquistition	0 - 10 V DC
ADC Chip	ADS1115
Module Address	I2C - 0x48

[http://www.cartft.com/catalog/il/2804]

Resolution	16bit
Complementary	
Local signalling	1 LED green for PWR
Electrical connection	Removable screw terminal block for inputs and outputs (pitch 5.08 mm)
	Top hat type TH35-15 rail conforming to IEC 60715
Mounng support	
	Top hat type TH35-7.5 rail conforming to IEC 60715
Height	86.00 mm
Depth	59.00 mm
Width	35.00 mm
Product weight	0.12 Kg
Environment	
Relave humidity	1095% without condensation in operation
IP degree of protecon	IP20
Operating altitude	02000m
Storage altitude	03000m
Shock resistance	15 gn for 11 ms
Operating temperature	-40 to +85 'C
Analog Module communication	
Module Type	ADS1115
Communication	2C
Module Address	0x48
Command set	Refer datasheet