

Rear Panel I/O	<ul style="list-style-type: none"> - 2* USB3.1 (Gen1) - 2* HDMI (Max. Resolution: 3840 x 2160@30Hz) - 2* RJ45 - 1* MIC/Line-out Combo (Realtek® ALC662VD) - 1* COM (RJ45 type) - 2* Antenna holes (WiFi only) - 1* DC-in jack (Lockable type)
Front Panel I/O	<ul style="list-style-type: none"> - 1* Power button - 1* Power LED, 1* HDD LED, 2* LAN LED - 2* USB3.1 (Gen1) - 1* AT / ATX mode Switch
Power Source	<ul style="list-style-type: none"> - AC to DC Adapter / AC 90~240V_DC12V_5A_60W - MT95-90 MB_DC 12V input
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, ErP Ready
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD) (The test environment is closed and windless) - Storage Temperature: -40 ~ 80° C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
Dimensions	<ul style="list-style-type: none"> - 144 (W) x 116.9 (D) x 65 (H) mm
OS Support	<ul style="list-style-type: none"> - Windows 10, Linux