



359.00 EUR
incl. 19% VAT, plus [shipping](#)

- Auto-Dimmer !
- Audio speakers !
- Auto-PowerOn !
- Slim design !

Support: [800x480 Driver \(Windows 7\)](#)

The new CTF-1020 TFT-Display is the latest development from CarTFT.com and comes with many nice features. In any case it is the ideal display- and input-unit for your Laptop, CarPC or HTPC. With the touchscreen functionality you easily can control your PC. The brilliant VGA-display ensures a maximum readability and sharpness.

New : LED-Backlight-Technology, with optimized color saturation enabling particular high and shining display. The scale of displayable color nuances is increased by 45% because of the new technology. Conventional LCDs are based on CCFL backlight, which can display approx. 72% of the standard color scale of NTSC (National Television Systems Committee). With LED-Backlight-Technology 104% of the NTSC-color scale can be displayed. This results in displaying in a highly realistic manner.

The device has integrated Stereo-speakers, a rear camera input and the Auto dimmer sensor in the front will enable perfect viewing pleasure also during the night.

AC-Adapter for home usage and a car cigarette lighter adapter is included as well as the IR-remote-control unit and the extra long (2,5 meters) All-In-One connector cable.

The CTF-1020 can be used with any PC/MAC with VGA- and USB port.

Driver-Download, compatible with :

- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat,Mandrake,..
- Macintosh OS 9.x, 10.x
- DOS,..

| Spezifikationen | |
|------------------------|--------------------------|
| Screen size | 10.2" digital |
| Aspect Ratio | 16:9 wide TFT screen |
| Dot Resolution | 2400x480= 1,152,000 dots |
| Physical Resolution | 800x480 |
| Supported Resolutions | 640x480-1920x1080 |
| Color configuration | RGB stripe |
| Power input | DC 12/24V |

| | |
|------------------------------|--|
| <i>Power consumption</i> | max. 12W |
| <i>Video system</i> | 3x Video inputs (PAL/NTSC) 1x VGA input |
| <i>Dimensions</i> | Display Case : 250mm x 176mm x 26mm Display : 222 x 134 mm |
| <i>Video input signal</i> | 1.0Vp-p, composite video |
| <i>Brightness</i> | 400 cd/m ² |
| <i>Contrast</i> | 400:1 |
| <i>Vibration</i> | IEC68-2-6 |
| <i>Operating Temperature</i> | -30° to 85°C |
| <i>Features</i> | Full function OSD control (english) |
| | Built-in Stereo-speakers |
| | Auto-Dimmer for TFT backlight |
| | Auto Power On/Off |
| | 5-wire Touchscreen |
| | VESA compliant mounting holes (75mm) + metal rail |
| | Automatic switching to rear camera (by signal detection on AV3) |
| <i>What is included ?</i> | - 10.2" VGA Touchscreen TFT with Video/Audio-support |
| | - Infrared Remote Control |
| | - Car dash VESA mounting bracket |
| | - Touchscreen pencil |
| | - VGA/Video/Audio/Touchscreen-cable (all-in-one !) 2.5 meters length |
| | - Power Adapter f. EU 230V |
| | - Cigarette Lighter Adapter |
| | - Manual |



Displays with [True-800x480-Support](#) achieve a pixel accurate view at 800x480@70Hz